



Domestic dehumidifiers that are compact, portable and easy to move and setup. According to European Regulation number 517/2014, concerning to the greenhouse gases. Available in 4 versions according to the dehumidification capacity: 12L., 16L., 20L. and 30L.

Features:


- Super-silent rotary compressor.
- Electronic humidistat, allowing you to select the required level of humidity, and ambient humidity indicator.
- 2 speeds and 3 operating modes: MANUAL, CONTINUOUS & AUTOMATIC. Automatic mode will select the level of humidity based on the ambient temperature.
- Programmable 1-24 hour run-on timer.
- Anti-frost function: activates when the ambient temperature falls below approximately 15°C.
- Automatic reset in the event of a power cut.
- Warning sign when the water tank saturates.
- Automatic shut-off function: activates when the water tank is full.
- Carrying handles.
- Operating temperature: 5-32°C.



Control panel
Humidity indicator display.



Removable water tank.



Easy-clean air filter.



Continuous water drainage device.



Wheels.

TECHNICAL CHARACTERISTICS

Model	Voltage 50Hz (V)	Power (W)	Maximum absorbed current (A)	Sound power level (dB(A))	Dehumidification capacity (litres/24H.) (30°C/80 H.R.)	Water tank capacity (L.)	Surface area of influence* (m²)	Coolant	Global-Warming Potential (GWP)	Speeds	Colour RAL	Weight (kg)	Dimensions LxAxH (mm)
DHUM-12 EN	230	200	1,4	40	12	2	30	R290	3	2	White 9003 / Black 9005	12	365x220x490
DHUM-16 EN	230	350	2,1	42	16	2	40	R290	3	2	White 9003 / Black 9005	13	365x220x490
DHUM-20 EN	230	415	2,2	42	20	2	45	R290	3	2	White 9003 / Black 9005	13	365x220x490
DHUM-30 EN	230	520	2,3	46	30	7	50	R290	3	2	White 9003 / Black 9005	19	481x286x628

* Information provided as guidance for ceiling heights of 2.5 m.

These models contain fluorinated greenhouse gases regulated by the Kyoto Protocol. Hermetically sealed equipment.